

HIGEN		INDUCTION MOTOR DATA SHEET		40 HP - 4 P	
MODEL: KMH-40HU1F		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF300		OUTPUT 30 kW 40 HP	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 4 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-△ <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> SOFT-STARTER		
PROTECTION		IP 54		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>			
FREQUENCY		60 Hz		RATED VOLTAGE 380 V V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.15		NO LOAD 21.0 A A A	
INSULATION CLASS		F CLASS		FULL LOAD 58.3 A A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 504.7 A A A	
RES. METHOD		105 °C		EFFICIENCY	
THERMO. METHOD		°C		AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 93.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40 °C		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 84.0 %	
MOUNTING		<input type="checkbox"/> B3 <input checked="" type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 1760 rpm	
BEARING	TYPE		BALL		
	DEW-DE		6312ZZ / 6309ZZ		
	LUBRICANT		GREASE		
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		TORQUE	
SHAFT				FULL LOAD 16.6 kg-m 100%	
EXTENSION		SINGLE		LOCKED ROTOR 31.5 kg-m 190%	
EXTERNAL THRUST				BREAKDOWN 36.5 kg-m 220%	
TERMINAL BOX				NOISE LEVEL 84.0 dB(A)	
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		VIBRATION 30.0 μm	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		ALLOWABLE LOAD GD² REFERRED TO MOTOR SHAFT	
BOX LOCATION		LEFT (Viewed from Drive end)		(AT DIRECT ON-LINE) 97.5 kg-m²	
APPLICATION STANDARDS		KS.IEC		Motor GD² 0.8623 kg-m²	
				MOTOR APPROX. WEIGHT 215.0 kg	
				PAINTING MUNSSELL NO. 5 PB 6/1.5	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-V-180L-CAT		
WINDING			S-T CURVE ST-KMH-40HU1		
TYPE			TERMINAL BOX DIMENSION TB-3040KK2003		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN STANDARD.					
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
			2008-05-02 J.S.PARK J.S.PARK H.T.KIM		