

HIGEN		INDUCTION MOTOR DATA SHEET		22 kW 6 P 180L	
MODEL: KMP-30HV8		CUSTOMER :		COIL SPEC NO.:	
APPLICATION:		PROJECT NAME:		REV. NO : 0	
QUANTITY :		SETS			
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		180L		OUTPUT 22 kW	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 6 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F	
PHASE		3 PHASE		<input type="checkbox"/> VECTOR DRIVE	
SERVICE FACTOR		1.15		RATED VOLTAGE 440 V V	
INSULATION CLASS		F CLASS		FREQUENCY 60 Hz	
TEMP.RISE AT FULL LOAD (at S.F 1.0)		CURRENT			
RES. METHOD 80 deg		NO LOAD		A A	
THERMO. METHOD deg		FULL LOAD		39.8 A A	
		STARTING		238.8 A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		EFFICIENCY	
ALTITUDE 1000 m				AT 1/2 LOAD %	
HUMIDITY 80 %				AT 3/4 LOAD %	
AMBIENT TEMPERATURE -10~40				AT FULL LOAD 93.0 %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		POWER FACTOR	
NEMA DESIGN B				AT 1/2 LOAD %	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 3/4 LOAD %	
BEARING		TYPE BALL / BALL		AT FULL LOAD 78.0 %	
DEW-DE 6312ZZC3 / 6309ZZC3		SPEED (AT FULL LOAD)		1170 rpm	
LUBRICANT GREASE		TORQUE			
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		FULL LOAD 18.3 kg-m 100%	
ROTATION(Facing Drive End)		<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		LOCKED ROTOR 25.6 kg-m 140%	
SHAFT				BREAKDOWN 33.0 kg-m 180%	
EXTENSION		SINGLE		NOISE LEVEL 79.0 dB(A)	
EXTERNAL THRUST		-		VIBRATION 30.0 μm	
TERMINAL BOX		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		(AT DIRECT ON-LINE) 247.0 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		Motor GD ² 1.1909 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT 225 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING	
				MUNSELL NO. 5PB 2.5/8.0	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-180LTFCHLS-2		
WINDING NO			SPEED-TORQUE CURVE ST-P22KV8T180L-1		
TYPE -			TERMINAL BOX DIMENSION TB-MS180NZ-1		
BEARING NO					
TYPE -					
SPACE HEATER NO					
RATING -					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.			2. PREMIUM EFFICIENCY MOTOR.		
TE : TOTALLY ENCLOSED DP : DRIP PROOF			DATE		
FC : FAN COOLED SC : SELF COOLED			PREPARED		
			CHECKED		
			APPROVED		
			2016-04-12		
			H.S.LEE		
			K.I.HA		
			K.I.HA		